

## RESIDENTIAL RESILIENT MAINTENANCE

---

Proper care will help protect and maintain the appearance and performance of your resilient floor.

Below are the types of care covered in this document:

1. Post-Construction Maintenance
2. Preventative Maintenance
3. Routine Maintenance
4. Spot and Spill Removal.

During construction, dust and joint compound can be deposited on the flooring. If it is not completely removed and then wet mopped, it will create a haze on the surface of the flooring.

### **POST-CONSTRUCTION MAINTENANCE**

Sweep floor clean. Dry mop floor using distilled water and a microfiber mop pad or appropriate floor vacuum to remove dust particulate from the floor.

Spray neutral pH cleaner onto the floor. Use a microfiber wet mop pad to mop the floor with cleaner. If pad becomes dirty, be sure to replace the pad with a new microfiber wet mop pad. Mop floor in sections.

Always rinse the floor with distilled water only by mopping with distilled water to remove any remaining residue from the floor.

In the event where dry wall dust/construction dust is mopped with distilled water only, a residue film will appear on the floor after drying. Use the process below to remove the film from the floor.

### **PROCESS TO REMOVE CONSTRUCTION RESIDUE OR CLOUDY FILM FROM RESILIENT FLOORING**

1. Dry mop floor with distilled water to remove any construction dust or exterior soil tracked onto the flooring. Use microfiber dry mop pad. If microfiber dry mop pad gets dirty, replace pad with a clean pad.
2. Spray neutral pH cleaner onto the floor. Clean floor in sections. For smooth surface, use a low rpm (175 rpm) buffer with a 3M red pad on flooring with neutral pH cleaner applied to the floor to remove the residue film. (Never Dry Buff). For embossed or textured flooring, use a cylindrical brush scrubber, such as the Clark MA10 12E Scrubber and a neutral pH floor cleaner applied to the floor to remove the residue film.
3. Using a wet microfiber mop pad, rinse with distilled water only to remove any remaining residue from the flooring. When wet mop pad becomes dirty, be sure to replace the pad with a new microfiber wet mop pad.
4. Repeat steps #2 and #3, if necessary.

# RESIDENTIAL RESILIENT MAINTENANCE

---

## PREVENTATIVE MAINTENANCE

- Always protect floors when moving heavy objects to prevent permanent scratches and tears.
- Adhering tape to the surface of your resilient flooring could damage the surface.  
**Do not** use tape to secure floor protection directly to the floor during construction or renovation. Instead, adhere tape to the material used to protect the floor and secure it to the base molding along the wall. A material such as ram board can also be used to protect your flooring.
- Use appropriate wide floor protectors under tables, chairs, and any other heavy home furnishing to avoid permanent damage.
- Walk-off mats should be used at all entrances to absorb soil and moisture. If mats are placed directly on top of the resilient floors, **use mats without latex or rubber backings to avoid possible discoloration.**
- Use appropriate window coverings to avoid direct sunlight as this can fade the color of the flooring.
- Do not use mop and shine products on your resilient flooring.
- Some disinfectants contain chemicals that can stain, discolor, and cause general harm to your flooring product. Take care to choose pH neutral products only.

## ROUTINE MAINTENANCE

- Daily removal of dirt and dust is important to prevent particles from abrading the surface of resilient floors. Sweeping, dust mopping, and vacuuming are recommendations to remove soil particles that can result in scratches and worn appearances. Do not use vacuums with rotating beater bars on hard surfaces.
- Periodic wet cleaning will be necessary to help maintain the floor's appearance. Always pre-vacuum or dust mop before any type of wet cleaning. Appropriate vinyl floor cleaning equipment and cleaning agents (neutral pH floor cleaners) are recommended. Do not use abrasive cleaners or cleaning agents that leave dull residues on the surface of the floors. Follow the cleaning manufacturer's instructions for damp mopping and application. If rinsing is necessary, use clean water and expedite drying with air movers or fans.
- Neutral pH floor cleaner is recommended for general spotting and cleaning. Avoid using mop and shine products on your resilient flooring. Products containing bleach and steam mops are not recommended.

## SPOT & SPILL REMOVAL

Our flooring products are engineered to resist and minimize common staining.

- Absorb wet spills as quickly as possible by blotting with paper or cloth towels. Rinse with water if necessary and blot dry.
- Dried spots should be removed by gentle agitation and rinsed with water. Blot dry.
- Use products formulated for vinyl floor cleaning. Do not use detergents or abrasive cleaners since these products can leave a dull residue.
- Use rubbing alcohol (isopropyl alcohol) with a clean white cloth for spots requiring a solvent type of cleaner that water and cleaning agents cannot remove.
- *Please note that some stain conditions may become permanent.*

Safety Caution: The surfaces of resilient floors change during wet cleaning and finish applications. Use appropriate safety measures.