

Description:	WPC Core Floating Floor with Attached 2mm IXPE Underlayment
Warranty:	Lifetime Limited Residential Wear Warranty Lifetime Limited Structural Warranty Lifetime Limited Waterproof Warranty 15 Year Limited Commercial Wear Warranty
Installation:	Float, Glue Down
Size/Packaging:	7.04" x 59.84" x 8.5 mm planks 23.43 sq. ft./carton, 8 planks per carton, 38 lbs. per carton, 60 ctns per pallet
Density:	2000 kg/m3
Pattern Repeat:	5 - 8 planks
Construction:	0.5 mm/20 mil Wear Surface 1.0 mm Vinyl Base Layer 5.0 mm WPC Core 2.0 mm IXPE Underlayment
Edges/Ends:	Pressed Bevel
Locking Profile:	Unilin Angle Tap
Wear Finish:	UV - Ceramic
Gloss Level:	4% - 6%

TEST DATA

ASTM E492-09 Impact Sound Conduction	IIC 62
ASTM E90-09 Airborne Sound Conduction	STC 63
ASTM F-970-15 Static Load Limit:	0.03 mm @ 250 lbs Pass
ASTM F2199 Dimensional Stability:	0.01%
ASTM F1914 Short-Term Indentation:	Pass
ASTM-E648-19a Critical Radiant Flux:	Pass, Class1
ASTM-E662-21a Smoke Density:	Pass, Non-Flaming 493

Certifications: GREENGUARD GOLD Certified

Country of Origin: Manufactured in Vietnam